

## ControlEdge™ RTU Process Controller

### Product Information Note

ControlEdge™ RTUs are powerful, modular and scalable controllers capable of all remote automation and control applications. They provide improved management of field assets through simplified and efficient remote monitoring, diagnostics, and management. Reduce equipment monitoring and diagnostics from hours to minutes. Experion® SCADA configuration time is reduced by 80%.

With Honeywell's ControlEdge RTU process controller, users have an edge into realizing the best utilization of their distributed assets through efficient remote monitoring, diagnostic and asset management capabilities, while ensuring low total cost of ownership.

#### Key Features

- Lowest power consumption in its category at a typical 1.9W (Non-redundant controller with onboard I/O)
- Native controller redundancy. No special programming
- Temperature range -40 to 75°C (-40 to 167°F)
- High reliability with designed thermal paths
- HART enabled onboard and expansion I/O modules. No extra hardware required for Digital HART data and diagnostic access. For use in RTU program and remotely via HART IP
- Efficient wiring and configuration saving installation and maintenance time
- Transient Suppression on every I/O channel and every communication port
- An onboard wireless I/O solution to integrate ISA100 instruments
- Foundation Fieldbus I/O
- Asset management of connected HART, Foundation Fieldbus and ISA 100 devices via Honeywell's Field Device Manager
- A powerful IEC 61131-3 programming environment
- Bulk Firmware upgrade to controllers and IOMs
- Liquids and Gas flow calculations in the same controller
- Gas and Liquid custody transfer Meter Runs compliant to API 21.1 and API21.2 standards
- Flexible communication options, local and remote
- Industry standard protocols of Modbus, DNP3 and user defined protocol
- Datalogging to on board memory or optionally on local SD card



Figure 8. Controller with Onboard I/O Module

*controllers providing secure connectivity through all levels of process and business functions, optimized operations, and maintenance efficiencies to meet your diverse automation needs.*

### BENEFITS

Lower Installation  
Cost

Reduce Windshield  
time

Better Remote  
Decisions

Reduce Onsite Time

Better Availability

Secure  
Communication

More than  
Telemetry

- Hazardous area certified to FM/CSA Class I Division 2, IECEx Zone 2 and ATEX Zone 2

**The Lowest Power Consumption & High Reliability**

Solar power is a common requirement in remote applications. The more power consumed, the bigger the batteries, solar panels and infrastructure to hold them need to be, all adding up to an expensive exercise.



ControlEdge RTU has one of the lowest power consumptions on the market at a typical 1.9 Watts, even when using HART. When HART is required, other RTUs require additional hardware, consuming even more power, whereas ControlEdge RTU has HART onboard.

The follow-on effect of consuming less power is that there is less heat produced. This, coupled with an aluminium body and designed thermal paths, means ControlEdge RTU has less component stress which equates to higher reliability. Even in tropical and desert environments, either minimal or no cooling is required.

**Endures Tough Environments**

ControlEdge RTU has been designed to withstand the toughest environments, with an operating temperature range of -40 to 75°C in humidity of 5% to 95%. Most other RTUs only go up to 70°C. ControlEdge RTU has conformal coating to G3 and is hazardous area certified to FM/CSA Class I Division 2, IECEx Zone 2 and ATEX Zone 2.



RTUs are typically placed next to metal infrastructure such as pipelines, so to reduce risk

of transient surges, every I/O channel and every communication port on ControlEdge RTU has transient suppression

*Reduce onsite time through Wireless I/O*

**High Performance Controller**

With modern processors, ControlEdge RTU has the power for today’s applications and spare reserve to meet tomorrow’s needs. ControlEdge RTU comes in two forms: Non-redundant controller with onboard I/O module and redundant controller. Both support expansion I/O modules.

**Native Controller Redundancy**

Honeywell’s redundancy is ready to go and ISA Secure Level 2 certified. There is no need to program any differently from a non-redundant controller. ControlEdge RTU takes away the complexity. No additional infrastructure is required to synchronize the data between CPMs and to connect with I/O modules. Project configuration can be stored in controller and retrieve when required.



Figure 1. Redundant controller with two expansion I/O modules

**Inputs / Outputs**

**2020 Platform I/O Modules, HART Enabled**

ControlEdge RTU supports onboard and expansion I/O modules.

28 Channel Mixed I/O Module:

Channel type	Qty
Analog Inputs:	8
Analog Outputs:	2
Digital Inputs:	10
Digital Outputs:	6
Pulse Inputs:	2



By having built-in HART, ControlEdge RTU has no requirement for separate expensive and

power consuming HART I/O modules or third party components.

### Foundation Fieldbus I/O

ControlEdge RTU supports Foundation Fieldbus I/O through the proven Series C FIM4 (Foundation Fieldbus interface module).

### Wireless I/O

By connecting a Field Device Access Point (FDAP), ControlEdge RTU provides an onboard Wireless I/O solution for ISA100 devices. These wireless devices appear as native I/O. They are programmed and managed with the same configuration tool, ControlEdge Builder. You benefit from the same smart device capabilities as wired smart devices. Wireless I/O is effective when traditional wiring is expensive, difficult or at risk of damage.

### The Value of Smart Data: HART, ISA 100 and Foundation Fieldbus Devices

Distributed operations can require crews of field operators that travel each day over long distances and dangerous terrain. ControlEdge RTU can help bring that requirement to an end. It is not only a large operating expense, but is also unsafe—and that is just the trip to site. The traditional RTU strengths of data logging and good sub-system communications with local devices, alongside smart device integration with HART, Foundation Fieldbus or Wireless I/O, is enabling better fault modeling, both direct on the RTUs and at central locations. This means that each Field Operator is much more productive and can manage more remote sites than without the implementation of ControlEdge RTU.




Figure 2. HART data accessed by RTU, Experion & FDM

In **Error! Reference source not found.**, we show ControlEdge RTU accessing both the HART device’s digitally accurate secondary variable and its diagnostic data. After receiving a common alarm from the RTU, the operator might go to a dynamically scanned detail page to diagnose the fault further or optionally use Honeywell’s Field Device Manager to connect through to the HART device using HART IP. Wireless devices provide a similar experience and can also be managed by Field Device Manager.

For more information on smart device management, refer to the Field Device Manager (FDM) Product Information Note.

### Efficient Wiring and Assembly

Wiring built-in terminals can be a frustrating and error prone exercise for an installer. To combat this, ControlEdge RTU comes with removable field terminals allowing the installer to hold the terminals in their hand for wiring even with gloves on. In addition, the terminals are printed with the I/O type and number giving the installer positive identification of the terminal against the ferrule label. Combined, this saves upfront installation cost and reduces wiring errors.




Figure 3. Positive identification on removable terminals



Figure 4. RTU Processor ease of removal from IOTA

## Flexible Communications

### Standard Protocols

Two features that really differentiate RTUs from PLCs are their communications capability and with that, data logging and history backfill. RTUs need to efficiently manage unreliable, low bandwidth networks. They need to communicate as a slave device to a remote SCADA system, sometimes over a redundant link on two different mediums; but also as a master to local subsystems like gas chromatographs and smart drives. In a “store and forward” type strategy, if communications to SCADA are interrupted, then the RTU needs to buffer data. Once communications are restored, then history is backfilled to SCADA.

ControlEdge RTU covers all the scenarios by supporting SCADA protocols such as Modbus and DNP3 over:

- Two Ethernet ports
- Two RS-232 serial ports
- Two RS-485 serial ports

With DNP3, history recovery back to Experion is natively supported. To allow this backfill to be ‘tuned’ to the available network bandwidth, analog input deadbands can be adjusted remotely from Experion. It also supports multiple masters on the same port.

### User Defined Protocol

ControlEdge RTU gives more flexibility on protocol support by providing necessary infrastructure to communicate to serial devices that understands nonstandard protocol.

### On-board Applications

#### Robust Data Logging Ensures Data Availability

ControlEdge RTU has data logging capabilities to record values to data files in flash memory or the onboard SD card, (optional), supporting up to 32GB of data. This ensures important data is never lost and is available for future analysis. The data files can be retrieved remotely through ControlEdge Builder or a utility and then displayed or imported by many Windows applications. ControlEdge RTU can log data

continuously at a pre-defined interval, or data logging can be event-triggered.

### Meter Runs turn your RTU into a Flow Computer / EFM

ControlEdge RTU Meter Run option provides an API21.1 & API21.2 compliant gas & liquid custody transfer solution. Meter Runs work alongside the rest of the RTU control program and are easily configured with a 5 step wizard. Data logs and audit trails can be imported by Experion for use in gas management systems. They are also available through Enron Modbus protocol.

*RTU is more than Telemetry, turn RTU in to Flow Computer / EFM to measure both Gas and Liquid*




Figure 5. RTU Builder, an IEC 61131-3 Environment

### ControlEdge Builder — An Integrated Configuration Environment

ControlEdge Builder is the configuration tool to design, configure, program and maintain your ControlEdge RTU or ControlEdge PLC. ControlEdge Builder is fully compliant to IEC 61131-3 supporting all five programming languages.

- Ladder Diagram (LD)
- Function Block Diagram (FBD)
- Structured Text (ST)
- Instruction List (IL)
- Sequential Function Chart (SFC)

*Low total solution cost through integration with Experion SCADA or Elevate*

In addition to the basic function blocks that come with an IEC 61131-3 environment, ControlEdge Builder includes Honeywell designed function blocks derived from our extensive industry experience and family of market leading automation controllers. Function blocks include PID, Device Control, Auto Manual, Fan Out, Ratio Control, Position Proportional, Totalizer and AGA/API/IEC gas and liquids calculations, just to name just a few. There are also ControlEdge RTU specific function blocks such as HART Command 3, 'read dynamic variables' and HART Command 48, 'read diagnostics status'.

ControlEdge Builder is designed to connect locally or remotely to the RTUs using TCP/IP. Personnel can program on site or from a remote central location to save time and mitigate the need for site works.

### Remote Bulk Firmware Upgrades

Being able to remotely upgrade RTU and wireless device firmware is very important when there are hundreds of RTUs geographically distributed. To account for low bandwidth, unreliable networks, remote firmware upgrading for controllers and IOMs from ControlEdge Builder is a two-step process ensuring uptime of the RTU and reliability of the result.

### Remote Diagnosis

Just as important as being able to remotely program and upgrade ControlEdge RTU is being able to remotely diagnose the health of the RTU. ControlEdge Builder provides a high definition analysis of the health scenario, leading to fewer site visits.

### Simulation

Improve your project schedule by simulating the controller. Simulated controller supports execution of the program and can communicate with SCADA using Modbus. Multiple simulated controller can be created.

### Experion SCADA/Elevate and ControlEdge RTU

Through use of open protocols, ControlEdge RTU is designed to work with any SCADA system.

When combined with Experion SCADA/Elevate, it is the perfect solution. With support for up to 5,000 RTUs per server and further server based expansion through the patented Distributed System Architecture (DSA™), Experion is a highly scalable system with the highest level of reliability, safety and security.

### Faster, Less Error Prone SCADA Configuration & Maintenance

ControlEdge RTU integration in Experion SCADA reduces the time to configure and maintain the combined solution by 80%.

- Automatic SCADA point configuration and maintenance based on RTU program
- Standard System Status Displays & Alarms for ControlEdge RTU hardware
- Meter templates aligned to ControlEdge RTU Meter Runs




Figure 6. Experion Equipment Templates

### **For More Information**

Learn more about how Honeywell's ControlEdge RTU Process controller at our website [www.honeywellprocess.com](http://www.honeywellprocess.com) or contact your Honeywell Account Manager.

### **Honeywell Process Solutions**

1250 West Sam Houston Parkway South  
Houston, TX 77042

Honeywell House, Skimped Hill Lane  
Bracknell, Berkshire, England RG12 1EB UK

Building #1, 555 Huanke Road,  
Zhangjiang Hi-Tech Industrial Park,  
Pudong New Area, Shanghai 201203

[www.honeywellprocess.com](http://www.honeywellprocess.com)

Experion® is a registered trademark of Honeywell International Inc.  
ControlEdge™ and DSA™ are trademarks of Honeywell International Inc.

PN-17-27-ENG  
September 2019  
© 2017 Honeywell International Inc.

**Honeywell**